

W.E.F. 01-04-2023

Product	Description	Type	Range	Reading	Graduation	Price (₹)*	
	PLUNGER TYPE DIAL GAUGE (MODEL 40)	K39	5 mm	0.01 mm	0-50-0	2,420	
		K40	5 mm	0.01 mm	0-100	2,420	
		K41	0.25"	0.001"	0-50-0	2,660	
		K42	0.25"	0.001"	0-100	2,660	
		K35	10 mm	0.1 mm	0-10	2,790	
		K36	5 mm	0.01 mm	0-50	2,910	
		K43	0.25"	0.0005"	0-50	2,920	
		K40Z	0.8 mm	0.01 mm	40-0-40	2,670	
	PLUNGER TYPE DIAL GAUGE (MODEL 56)	KZ	0.8 mm	0.01 mm	40-0-40	1,680	
		K01	10 mm	0.01 mm	0-50-0	1,550	
		K02	10 mm	0.01 mm	0-100	1,550	
		K03	5 mm	0.01 mm	0-50-0	1,610	
		K04	5 mm	0.01 mm	0-100	1,610	
		K05	10 mm	0.1 mm	0-10	1,520	
		K06A	25 mm	0.1 mm	0-10	2,130	
		K07	30 mm	0.01 mm	0-100	3,380	
		K08A	25 mm	0.01 mm	0-100	2,110	
		K09	2 mm	0.002 mm	0-10-0	3,380	
		K10	2 mm	0.002 mm	0-20	3,380	
		K11	5 mm	0.002 mm	0-10-0	4,030	
		K12	5 mm	0.002 mm	0-20	2,850	
		K13A	12 mm	0.002 mm	0-10-0	6,530	
		K14A	12 mm	0.002 mm	0-20	6,530	
		K17S	1 mm	0.001 mm	0-100-0	3,280	
		K20	50 mm	0.01 mm	0-100	5,570	
		KY	0.08"	0.001"	40-0-40	1,850	
		K50	1"	0.001"	0-100	2,930	
		K51	0.5"	0.001"	0-50-0	2,230	
		K52	0.5"	0.001"	0-100	2,230	
		K53	0.5"	0.0005"	0-25-0	2,730	
		K54	0.5"	0.0005"	0-50	2,730	
		K61	0.2"	0.0001"	0-50-0	4,900	
		K62	0.2"	0.0001"	0-100	4,900	
		K63A	0.5"	0.0001"	0-50-0	7,900	
		K64A	0.5"	0.0001"	0-100	7,900	
		K21	2"	0.001"	0-100	5,570	
	PLUNGER TYPE DIAL GAUGE (MODEL 88)	K72	50 mm	0.01 mm	0-100	7,480	
		K76	2"	0.001"	0-100	7,910	
	PLUNGER TYPE DIAL GAUGE (MODEL 100)	K100	100 mm	0.01 mm	0-100	22,930	
	PLUNGER TYPE DIAL GAUGE (MODEL 105)	K101	2 mm	0.01 mm	0-50-0	7,090	
	HARDNESS TESTER DIAL (ROCKWELL) STANDARD	-	-	-	-	3,200	
	DIGITAL DIAL GAUGE (RS232 DATA OUTPUT) 'W' Series : IP67	W1	12.5 mm/0.5"	0.001 mm/0.00005"	-	20,640	
		W2	25 mm/1"	0.001 mm/0.00005"	-	21,680	
		W3	50 mm/2"	0.001 mm/0.00005"	-	37,210	
		W1A	12.5 mm/0.5"	0.001 mm/0.00005"	-	21,950	
		W2A	25 mm/1"	0.001 mm/0.00005"	-	22,910	
		W3A	50 mm/2"	0.001 mm/0.00005"	-	38,480	
		BAKER Proximity cable with RS232 interface suitable for BAKER digital dials W1, W2, W3					7,210
		BAKER Proximity cable with USB interface suitable for BAKER digital dials W1, W2, W3					7,210

W.E.F. 01-04-2023

Product	Description	Type	Range	Reading	Graduation	Price (₹)*
	DIGITAL DIAL GAUGE	V1	12.5 mm/0.5"	0.01 mm/0.0005"	-	6,680
		V2	25 mm/1"	0.01 mm/0.0005"	-	8,360
		V3	50 mm/2"	0.01 mm/0.0005"	-	22,170
		V1P	12.5 mm/0.5"	0.001 mm/0.00005"	-	12,890
		V2P	25 mm/1"	0.001 mm/0.00005"	-	15,490
	LEVER TYPE DIAL GAUGE (MODEL 29)	302P	0.8 mm	0.01 mm	0-40-0	4,630
		304	0.2 mm	0.002 mm	0-10-0	6,570
		Supplied with Ø 2 mm T.C. Ball Stylus fitted to the gauge & 1 mm T.C. Ball Stylus, Height Gauge Adapter, Ø 4 mm & Ø 8 mm Dovetail Spigot Assembly and Universal Calmp as standard accessories in a box.				
		302AP	0.8 mm	0.01 mm	0-40-0	3,670
		304A	0.2 mm	0.002 mm	0-10-0	5,840
		Supplied with Ø2 mm T.C. Ball Stylus & 8mm Dovetail Spigot Assembly fitted to the gauge				
	LEVER TYPE DIAL GAUGE LONG STYLUS (MODEL 29)	302L	0.8 mm	0.01 mm	0-40-0	6,480
		Supplied with 33mm long Ø 2mm T. C. Ball Stylus fitted to the gauge, Height Gauge Adapter, Ø 4 mm & Ø 8mm Dovetail Spigot Assembly and Universal Clamp as standard accessories in a box				
		302AL	0.8 mm	0.01 mm	0-40-0	5,640
		Supplied with 33 mm long Ø 2 mm T.C. Ball Stylus & Ø 8 mm Dovetail Spigot Assembly fitted to the gauge.				
	LEVER TYPE DIAL GAUGE (MODEL 38)	306P	0.8 mm	0.01 mm	0-40-0	5,290
		308	0.2 mm	0.002 mm	0-10-0	8,180
		Supplied with Ø 2mm T.C. Ball Stylus fitted to the gauge & Ø 1 mm T.C. Ball Stylus, Height Gauge Adapter, Ø 4 mm & Ø 8 mm Dovetail Spigot Assembly and Universal Calmp as standard accessories in a box.				
		306AP	0.8 mm	0.01 mm	0-40-0	4,040
		308A	0.2 mm	0.002 mm	0-10-0	7,330
		Supplied with Ø 2 mm T.C. Ball Stylus & Ø 8 mm Dovetail Spigot Assembly fitted to the gauge.				
	LEVER TYPE DIAL GAUGE LONG STYLUS (MODEL 38)	306L	0.8 mm	0.01 mm	0-40-0	7,090
		Supplied with 33 mm long Ø 2 mm T. C. Ball Stylus fitted to the gauge, Height Gauge Adapter, Ø 4 mm & Ø 8 mm Dovetail Spigot Assembly and Universal Clamp as standard accessories in a box.				
		306AL	0.8 mm	0.01 mm	0-40-0	6,240
		Supplied with 33 mm long Ø 2 mm T.C. Ball Stylus & Ø 8 mm Dovetail Spigot Assembly fitted to the gauge.				
	DIAL BORE GAUGE	K439	4-6 mm	0.01 mm	0-50-0	25,870
		K539	6-10 mm	0.01 mm	0-50-0	13,545
		K639	10-18 mm	0.01 mm	0-50-0	8,970
		K641	0.4"-0.7"	0.001"	0-50-0	9,180
		K703	18-50 mm	0.01 mm	0-50-0	8,880
		K709	18-50 mm	0.002 mm	0-10-0	10,720
		K717	18-50 mm	0.001 mm	0-100-0	11,010
		K753	0.7" - 2"	0.0005"	0-25-0	10,140
		K761	0.7" - 2"	0.0001"	0-50-0	11,430
		K803	50-150 mm	0.01 mm	0-50-0	9,680
		K809	50-150 mm	0.002 mm	0-10-0	11,460
		K817	50-150 mm	0.001 mm	0-100-0	11,730
		K853	2" - 6"	0.0005"	0-25-0	11,370
		K861	2" - 6"	0.0001"	0-50-0	12,660
		K903	150-250 mm	0.01 mm	0-50-0	18,450
		K909	150-250 mm	0.002 mm	0-10-0	20,030
		K917	150-250 mm	0.001 mm	0-100-0	20,440
		K953	6"-10"	0.0005"	0-25-0	19,250
		K961	6"-10"	0.0001"	0-50-0	20,100
		K1003	250-450 mm	0.01 mm	0-50-0	23,020
		K1009	250-450 mm	0.002 mm	0-10-0	24,770
		K1017	250-450 mm	0.001 mm	0-100-0	25,220
		K1053	10-18"	0.0005"	0-25-0	23,910
		K1061	10-18"	0.0001"	0-50-0	25,790
		K803-S	50-150 mm	0.01 mm	0-50-0	10,750
		K809-S	50-150 mm	0.002 mm	0-10-0	12,750
		K853-S	50-150 mm	0.0005"	0-25-0	12,100
		K861-S	50-150 mm	0.0001"	0-50-0	14,100
	DIAL SNAP GAUGE (WITHOUT DIAL GAUGE)	DS25	0-25 mm	-	-	7,550
		DS50	25-50 mm	-	-	7,800
		DS75	50-75 mm	-	-	8,890
		DS100	75-100 mm	-	-	9,320
		DS125	100-125 mm	-	-	10,820
		DS150	125-150 mm	-	-	11,610
		DS175	150-175 mm	-	-	13,920
		DS200	175-200 mm	-	-	15,120
	COMPARATOR STAND (PLAIN BASE)	CS150	Gauging Height 150 mm	Base Size 90 x 95mm	-	7,650
		CS200	Gauging Height 200 mm	Base Size 150 x 100mm	-	9,210
	COMPARATOR STAND (SERRATED BASE)	CS150-S	Gauging Height 150 mm	Base Size 90 x 95mm	-	7,950
		CS200-S	Gauging Height 200 mm	Base Size 150 x 100mm	-	9,800
	MICROMETER STAND	BMS100	-	-	-	1,270
	MAGNETIC STAND WITH FINE ADJUSTMENT	MSF	-	-	-	1,820
	MAGNETIC STAND	MS	-	-	-	1,700
	UNIVERSAL MAGNETIC STAND	UMS	-	-	-	3,590

W.E.F. 01-04-2023

Product	Description	Type	Range	Reading	Graduation	Price (₹)*
	DIAL THICKNESS GAUGE (130 series) (Throat Depth:30 mm)	K130/0	10 mm	0.1 mm	0-10	2,460
		K130/3	10 mm	0.01 mm	0-100	2,550
		K130/6	2 mm	0.002 mm	0-20	4,290
		K130/7	5 mm	0.002 mm	0-20	4,740
		K130/1	0.5"	0.001"	0-100	2,890
		K130/8	0.05"	0.0001"	0-100	4,710
		K130/9	0.2"	0.0001"	0-100	5,220
	Push Down Type 138 series (Throat Depth:50 mm)	K138/0	25 mm	0.1 mm	0-10	4,200
		K138/3	25 mm	0.01 mm	0-100	4,480
		K138/1	1.0"	0.001"	0-100	4,920
		K138/0L	25 mm	0.1 mm	0-10	4,570
		K138/3L	25 mm	0.01 mm	0-100	4,840
		K138/1L	1.0"	0.001"	0-100	5,330
	142 series (Throat Depth:100 mm)	K142/0	10 mm	0.1 mm	0-10	2,890
		K142/3	10 mm	0.01 mm	0-100	3,010
		K142/1	0.5"	0.001"	0-100	3,290
	145 series (Throat Depth:200 mm)	K145/0	10 mm	0.1 mm	0-10	3,530
		K145/3	10 mm	0.01 mm	0-100	3,640
		K145/1	0.5"	0.001"	0-100	3,940
	150 series (Throat Depth:200 mm)	K150/0	25 mm	0.1 mm	0-10	5,210
		K150/3	25 mm	0.01 mm	0-100	5,500
		K150/1	1.0"	0.001"	0-100	5,990
	DIGITAL DIAL THICKNESS GAUGE 130 (Throat Depth:30 mm)	K130/D	12.5 mm/0.5"	0.001mm/0.00005"	-	19,100
	142 (Throat Depth:100 mm)	K142/D	12.5 mm/0.5"	0.001mm/0.00005"	-	19,310
	138 (Throat Depth:50 mm)	K138/D	25 mm/1"	0.001mm/0.00005"	-	22,060
	145 (Throat Depth:200 mm)	K145/D	12.5 mm/0.5"	0.001mm/0.00005"	-	19,860
	150 (Throat Depth:200 mm)	K150/D	25 mm/1"	0.001mm/0.00005"	-	22,610
	VERNIER CALIPER	VC10	0-150 mm/0-6"	0.02 mm/0.001"	-	2,020
		VC20	0-200 mm/0-8"	0.02 mm/0.001"	-	3,220
		VC30	0-300 mm/0-12"	0.02 mm/0.001"	-	6,430
	VERNIER CALIPER WITH FINE ADJUSTMENT	VCF10	0-130 mm/0-5"	0.02 mm/0.001"	-	2,310
		VCF20	0-180 mm/0-7"	0.02 mm/0.001"	-	3,420
		VCF30	0-280 mm/0-11"	0.02 mm/0.001"	-	6,710
		VCF45	0-430 mm/0-17"	0.02 mm/0.001"	-	19,750
		VCF60	0-580 mm/0-23"	0.02 mm/0.001"	-	24,310
		VCF80	0-780 mm/0-31"	0.02 mm/0.001"	-	36,590
		VCF100	0-980 mm/0-39"	0.02 mm/0.001"	-	47,680
		VCF150	0-1500 mm	0.02 mm/0.001"	-	87,0000
		VCF200	0-2000 mm	0.02 mm/0.001"	-	1,39,000
	DIAL CALIPER	DC10	0-150 mm	0.02 mm	-	3,590
		DC20	0-200 mm	0.02 mm	-	6,020
		DC30	0-300 mm	0.02 mm	-	8,010
	DIGITAL CALIPER	ED10	0-150 mm/0-6"	0.01 mm/0.0005 "	-	3,620
		ED20	0-200 mm/0-8"	0.01 mm/0.0005 "	-	5,450
		ED30	0-300 mm / 0-12"	0.01 mm/0.0005 "	-	7,370
	DIGITAL CALIPER	SDN10	0-150 mm/0-6"	0.01 mm/0.0005 "	-	5,830
		SDN20	0-200 mm/0-8"	0.01 mm/0.0005 "	-	7,730
		SDN30	0-300 mm/0-12"	0.01 mm/0.0005 "	-	10,160
	DIGITAL CALIPER (IP66)	SDN50	0-500 mm/0-20"	0.01 mm/0.0005 "	-	24,000
		SDN60	0-600 mm/0-24"	0.01 mm/0.0005 "	-	32,500
		SDN80	0-800 mm/0-32"	0.01 mm/0.0005 "	-	46,900
		SDN100	0-1000 mm/0-40"	0.01 mm/0.0005"	-	61,000
		SDN150	0-1500 mm	0.01 mm/0.0005"	-	88,600
		SDN200	0-2000 mm	0.01 mm/0.0005"	-	1,66,000
	DIGITAL CALIPER (IP67 & RS232 DATA OUTPUT)	ZD10	0-150 mm/0-6"	0.01 mm/0.0005 "	-	9,280
		ZD20	0-200 mm/0-8"	0.01 mm/0.0005 "	-	12,320
		ZD30	0-300 mm/0-12"	0.01 mm/0.0005 "	-	15,350
		Proximity cable for RS232 interface for ZD calipers				7,210
		Proximity cable for USB interface for ZD calipers				7,210
	DIGITAL DEPTH CALIPER	DDC10	0-150 mm/0-6"	0.01 mm/0.0005"	-	4,940
		DDC20	0-200 mm/0-8"	0.01 mm/0.0005"	-	6,050
		DDC30	0-300 mm/0-12"	0.01 mm/0.0005"	-	11,000
	INTERNAL GROOVE CALIPER	IGC10	10-120mm	0.010mm	0-100-0	20,770

W.E.F. 01-04-2023

Product	Description	Type	Range	Reading	Price (₹)*
	EXTERNAL MICROMETER	MMC25/INC1	0-25 mm/0-1"	0.01 mm/0.001"	1,700
		MMC25-1/INC1-1	0-25 mm/0-1"	0.001 mm/0.0001"	2,080
		MMC50/INC2	25-50 mm/1-2"	0.01 mm/0.001"	2,100
		MMC50-1/INC2-1	25-50 mm/1-2"	0.001 mm/0.0001"	2,825
		MMC75/INC3	50-75 mm/2-3"	0.01 mm/0.001"	2,390
		MMC75-1/INC3-1	50-75 mm/2-3"	0.001 mm/0.0001"	3,125
		MMC100/INC4	75-100 mm/3-4"	0.01 mm/0.001"	2,590
		MMC100-1/INC4-1	75-100 mm/3-4"	0.001 mm/0.0001"	3,560
		MMC125/INC5	100-125 mm/4-5"	0.01 mm/0.001"	3,190
		MMC125-1/INC5-1	100-125 mm/4-5"	0.001 mm/0.0001"	4,480
		MMC150/INC6	125-150 mm/5-6"	0.01 mm/0.001"	3,570
		MMC150-1/INC6-1	125-150 mm/5-6"	0.001 mm/0.0001"	4,760
		MMC175/INC7	150-175 mm/6-7"	0.01 mm/0.001"	4,150
	EXTERNAL MICROMETER (WITH INTERCHANGEABLE ANVILS)	MMI0-100/INI0-4	0-100 mm / 0-4"	0.01 mm/0.001"	9,950
		MMI0-150/INI0-6	0-150 mm / 0-6"	0.01 mm/0.001"	12,990
		MMI150-300/INI6-12	150-300 mm / 6-12"	0.01 mm/0.001"	18,000
		MMI200-300/INI8-12	200-300 mm/8-12"	0.01 mm/0.001"	15,550
	EXTERNAL MICROMETER (WITH ADD ON EXTENSION ANVIL)	MMI300-400/INI12-16	300-400 mm	0.01 mm	20,500
		MMI400-500/INI16-20	400-500 mm	0.01 mm	22,600
		MME500-600/INE20-24	500-600 mm	0.01 mm	30,200
		MME600-700/INE24-28	600-700 mm	0.01 mm	35,750
		MME700-800/INE28-32	700-800 mm	0.01 mm	39,650
		MME800-900/INE32-36	800-900 mm	0.01 mm	44,500
		MME900-1000/INE36-40	900-1000 mm	0.01 mm	52,500
	DIGITAL EXTERNAL MICROMETER (WITHOUT DATA OUTPUT)	DMM25	0-25 mm	0.001mm/0.00005"	7,980
		DMM50	25-50 mm	0.001mm/0.00005"	10,405
		DMM75	50-75 mm	0.001mm/0.00005"	12,320
		DMM100	75-100 mm	0.001 mm/0.00005"	14,250
		DMM125	100-125 mm	0.001 mm/0.00005"	15,710
		DMM150	125-150 mm	0.001 mm/0.00005"	17,625
		DMM175	150-175 mm	0.001 mm/0.00005"	18,870
	DIGITAL EXTERNAL MICROMETER (WITH DATA OUTPUT)	DMM200	175-200 mm	0.001 mm/0.00005"	20,755
		DMM25-1	0-25 mm	0.001 mm/0.00005"	9,865
		DMM50-1	25-50 mm	0.001 mm/0.00005"	12,560
		DMM75-1	50-75 mm	0.001 mm/0.00005"	16,075
		DMM100-1	75-100 mm	0.001 mm/0.00005"	18,065
		DATA CABLE P1502	-	-	5,605
	DISC MICROMETER ROTATING	MMC25-D/INC1-D	0-25 mm/0-1"	0.01 mm/0.001"	5,390
		MMC50-D/INC2-D	25-50 mm/1-2"	0.01 mm/0.001"	6,250
		MMC75-D/INC3-D	50-75 mm/2-3"	0.01 mm/0.001"	6,690
		MMC100-D/INC4-D	75-100 mm/3-4"	0.01 mm/0.001"	7,800
		MMC150-D/INC6-D	125-150 mm/5-6"	0.01 mm/0.001"	9,250
		MMC175-D/INC7-D	150-175 mm/6-7"	0.01 mm/0.001"	10,350
	DISC MICROMETER NON-ROTATING	MMC25-ND/INC1-ND	0-25 mm/0-1"	0.01 mm/0.001"	8,480
		MMC50-ND/INC2-ND	25-50 mm/1-2"	0.01 mm/0.001"	10,195
		MMC75-ND/INC3-ND	50-75 mm/2-3"	0.01 mm/0.001"	10,830
		MMC100-ND/INC4-ND	75-100 mm/3-4"	0.01 mm/0.001"	11,250
	POINT MICROMETER 15°	MMC25-P1/INC1-P1	0-25 mm/0-1"	0.01 mm/0.001"	5,430
		MMC50-P1/INC2-P1	25-50 mm/1-2"	0.01 mm/0.001"	7,060
		MMC75-P1/INC3-P1	50-75 mm/2-3"	0.01 mm/0.001"	8,520
		MMC100-P1/INC4-P1	75-100 mm/3-4"	0.01 mm/0.001"	10,650
	POINT MICROMETER 30°	MMC25-P2/INC1-P2	0-25 mm/0-1"	0.01 mm/0.001"	5,030
		MMC50-P2/INC2-P2	25-50 mm/1-2"	0.01 mm/0.001"	6,290
		MMC75-P2/INC3-P2	50-75 mm/2-3"	0.01 mm/0.001"	7,140
		MMC100-P2/INC4-P2	75-100 mm/3-4"	0.01 mm/0.001"	8,375
	SPLINE MICROMETER Ø 2.0 mm X 5.0 mm	MMC25-S2/INC1-S2	0-25 mm/0-1"	0.01 mm/0.001"	5,610
		MMC50-S2/INC2-S2	25-50 mm/1-2"	0.01 mm/0.001"	7,025
		MMC75-S2/INC3-S2	50-75 mm/2-3"	0.01 mm/0.001"	8,285
		MMC100-S2/INC4-S2	75-100 mm/3-4"	0.01 mm/0.001"	8,795
	SPLINE MICROMETER Ø 3.0 mm X 8.0 mm	MMC25-S3/INC1-S3	0-25 mm/0-1"	0.01 mm/0.001"	5,610
		MMC50-S3/INC2-S3	25-50 mm/1-2"	0.01 mm/0.001"	7,025
		MMC75-S3/INC3-S3	50-75 mm/2-3"	0.01 mm/0.001"	8,285
		MMC100-S3/INC4-S3	75-100 mm/3-4"	0.01 mm/0.001"	8,795

W.E.F. 01-04-2023

Product	Description	Type	Range	Reading	Price (₹)*
	TUBE MICROMETER ONE END SPHERICAL	MMC25-T1/INC1-T1	0-25 mm/0-1"	0.01 mm/0.001"	2,770
		MMC50-T1/INC2-T1	25-50 mm/1-2"	0.01 mm/0.001"	3,595
		MMC75-T1/INC3-T1	50-75 mm/2-3"	0.01 mm/0.001"	4,060
		MMC100-T1/INC4-T1	75-100 mm/3-4"	0.01 mm/0.001"	4,470
	TUBE MICROMETER BOTH END SPHERICAL	MMC25-T2/INC1-T2	0-25 mm/0-1"	0.01 mm/0.001"	2,915
		MMC50-T2/INC2-T2	25-50 mm/1-2"	0.01 mm/0.001"	3,790
		MMC75-T2/INC3-T2	50-75 mm/2-3"	0.01 mm/0.001"	4,145
		MMC100-T2/INC4-T2	75-100 mm/3-4"	0.01 mm/0.001"	4,715
	BLADE MICROMETER (BLADE THICKNESS 0.75 mm)	MMC25-B/INC1-B	0-25 mm/0-1"	0.01 mm/0.001"	8,035
		MMC50-B/INC2-B	25-50 mm/1-2"	0.01 mm/0.001"	8,560
		MMC75-B/INC3-B	50-75 mm/2-3"	0.01 mm/0.001"	8,840
		MMC100-B/INC4-B	75-100 mm/3-4"	0.01 mm/0.001"	9,775
		MMC125-B/INC5-B	100-125 mm/4-5"	0.01 mm/0.001"	15,050
		MMC150-B/INC6-B	125-150 mm/5-6"	0.01 mm/0.001"	17,610
		MMC175-B/INC7-B	150-175 mm/6-7"	0.01 mm/0.001"	19,230
		MMC200-B/INC8-B	175-200 mm/7-8"	0.01 mm/0.001"	20,695
	BLADE MICROMETER (BLADE THICKNESS 0.4 mm)	MMC25-BA/INC1-BA	0-25 mm/0-1"	0.01 mm/0.001"	9,650
		MMC50-BA/INC2-BA	25-50 mm/1-2"	0.01 mm/0.001"	10,275
		MMC75-BA/INC3-BA	50-75 mm/2-3"	0.01 mm/0.001"	10,615
		MMC100-BA/INC4-BA	75-100 mm/3-4"	0.01 mm/0.001"	11,740
		MMC125-BA/INC5-BA	100-125 mm/4-5"	0.01 mm/0.001"	19,010
		MMC150-BA/INC6-BA	125-150 mm/5-6"	0.01 mm/0.001"	22,245
		MMC175-BA/INC7-BA	150-175 mm/6-7"	0.01 mm/0.001"	24,290
		MMC200-BA/INC8-BA	175-200 mm/7-8"	0.01 mm/0.001"	26,140
	DEPTH MICROMETER	MMC25-DM60/INC1-DM60	0-25 mm/0-1"	0.01 mm/0.001"	5,110
		MMC25-1DM60/INC1-1DM60	0-25 mm/0-1"	0.001 mm/0.0001"	5,340
		MMC25-DM100/INC1-DM100	0-25 mm/0-1"	0.01 mm/0.001"	5,625
		MMC25-1DM100/INC1-1DM100	0-25 mm/0-1"	0.001 mm/0.0001"	5,875
		MMC25-DM60S/INC1-DM60S	0-25 mm/0-1"	0.01 mm/0.001"	5,875
		MMC25-1DM60S/INC1-1DM60S	0-25 mm/0-1"	0.001 mm/0.0001"	6,145
		MMC25-DM100S/INC1-DM100S	0-25 mm/0-1"	0.01 mm/0.001"	6,470
		MMC25-1DM100S/INC1-1DM100S	0-25 mm/0-1"	0.001 mm/0.0001"	6,755
		MMC100-DM60/INC4-DM60	0-100 mm/0-4"	0.01 mm/0.001"	6,255
		MMC100-DM100/INC4-DM100	0-100 mm/0-4"	0.01 mm/0.001"	6,800
		MMC150-DM60/INC6-DM60	0-150 mm/0-6"	0.01 mm/0.001"	7,815
		MMC150-DM100/INC6-DM100	0-150 mm/0-6"	0.01 mm/0.001"	8,600
	MICROMETER HEAD PLAIN	MM25-HP/IN1-HP	0-25 mm/0-1"	0.01 mm/0.001"	1,450
		MM25-1HP/IN1-1HP	0-25 mm/0-1"	0.001 mm/0.0001"	1,600
	MICROMETER HEAD THREADED	MM25-HT/IN1-HT	0-25 mm/0-1"	0.01 mm/0.001"	1,500
		MM25-1HT/IN1-1HT	0-25 mm/0-1"	0.001 mm/0.0001"	1,650
	MICROMETER HEAD DIFFERENTIAL	MMH-P	0-1 mm	0.001 mm	On Request
	TUBULAR INTERNAL MICROMETER	MMT150	50-150 mm	0.01 mm	7,370
		MMT300	50-300 mm	0.01 mm	9,930
		MMT500	50-500 mm	0.01 mm	13,644
		MMT1000	50-1000 mm	0.01 mm	18,000
		MMT1500	50-1500 mm	0.01 mm	22,253
	MECHANICAL INTERNAL MICROMETER	SMXTA1M/SMXTA1i	2-3 mm/0.080"-0.120"	0.001 mm/0.0001"	1,04,200
		SMXTA2M/SMXTA2i	3-6 mm/0.120"-0.250"mm	0.001 mm/0.0001"	1,41,580
		SMXTA3M/SMXTA3i	6-10 mm/1/4"-3/8"	0.002 mm/0.0001"	41,700
		SMXTA4M/SMXTA4i	10-20 mm/3/8"-3/4"	0.002 mm/0.0001"	56,450
		SXTA5M/SXTA5i	20-50 mm/3/4"-2"	0.005 mm/0.00025"	92,630
		SXTA6M/SXTA6i	50-100 mm/2"-4"	0.005 mm/0.00025"	1,31,820
		SXTA7M/SXTA7i	100-150 mm/4"-6"	0.005 mm/0.00025"	1,00,010
		SXTA8M/SXTA8i	150-200 mm/6"-8"	0.005 mm/0.00025"	1,45,330
	DIGITAL PISTOL - GRIP INTERNAL MICROMETER (XT HOLEMATIC) (IP67, RS232 & BLUETOOTH DATA OUTPUT)	SXTH1M-BT/SXTH1i-BT	2-6 mm/0.080"-0.25"	0.001 mm/0.00005"	2,72,460
		SXTH3M-BT/SXTH3i-BT	6-10 mm/1/4"-3/8"	0.001 mm/0.00005"	1,09,910
		SXTH4M-BT/SXTH4i-BT	10-20 mm/3/8"-3/4"	0.001 mm/0.00005"	1,27,330
		SXTH5M-BT/SXTH5i-BT	20-50 mm/3/4"-2"	0.001 mm/0.00005"	1,67,000
		SXTH6M-BT/SXTH6i-BT	50-100 mm/2"-4"	0.001 mm/0.00005"	1,84,780
		SXTH7M-BT/SXTH7i-BT	100-150 mm/4"-6"	0.001 mm/0.00005"	1,63,780
		SXTH8M-BT/SXTH8i-BT	150-200 mm/6"-8"	0.001 mm/0.00005"	2,16,840
		SXTH9M-BT/SXTH9i-BT	100-200 mm/4"-8"	0.001 mm/0.00005"	3,37,220
		SXTH10M-BT/SXTH10i-BT	6-20 mm/1/4"-3/4"	0.001 mm/0.00005"	1,49,760
		SXTH11M-BT/SXTH11i-BT	20-100 mm/3/4"-4"	0.001 mm/0.00005"	2,62,640
		SXTD1M-BT/SXTD1i-BT	2-6 mm/0.080" - 0.25"	0.001 mm/0.00005"	2,48,250
	DIGITAL INTERNAL MICROMETER (XT DIGITAL) (IP67, RS232 & BLUETOOTH DATA OUTPUT)	SXTD3M-BT/SXTD3i-BT	6-10 mm/1/4"-3/8"	0.001 mm/0.00005"	1,04,270
		SXTD4M-BT/SXTD4i-BT	10-20 mm/3/8"-3/4"	0.001 mm/0.00005"	1,18,980
		SXTD5M-BT/SXTD5i-BT	20-50 mm/3/4"-2"	0.001 mm/0.00005"	1,64,450
		SXTD6M-BT/SXTD6i-BT	50-100 mm/2"-4"	0.001 mm/0.00005"	1,82,200
		SXTD7M-BT/SXTD7i-BT	100-150 mm/4"-6"	0.001 mm/0.00005"	1,55,410
		SXTD8M-BT/SXTD8i-BT	150-200 mm/6"-8"	0.001 mm/0.00005"	2,05,840
		SXTD9M-BT/SXTD9i-BT	100-200 mm/4"-8"	0.001 mm/0.00005"	3,27,300
	LARGE DIAMETER 3-POINT DIGITAL INTERNAL MICROMETER (XT500) (IP67, RS232 & BLUETOOTH DATA OUTPUT)	SXT3000M-BT	300-400	0.001 mm/0.00005"	4,34,530
		SXT4000M-BT	400-500	0.001 mm/0.00005"	5,35,950
		SXT5000M-BT	300-500	0.001 mm/0.00005"	6,81,890
	LEVER TYPE INTERNAL MICROMETER (XTL)	SXTL3M-BT/SXTL3i-BT	6-10 mm/1/4"-3/8"	0.001 mm/0.00005"	1,09,850
		SXTL4M-BT/SXTL4i-BT	10-20 mm/3/8"-3/4"	0.001 mm/0.00005"	1,27,200
		SXTL5M/SXTL5i	20-50 mm/3/4"-2"	0.001 mm/0.00005"	1,64,910
		SXTL6M/SXTL6i	50-100 mm/2"-4"	0.001 mm/0.00005"	1,84,240

W.E.F. 01-04-2023

Product	Description	Type	Range	Reading	Graduation	Price (₹)*
	BACK PLUNGER TYPE DIAL GAUGE (MODEL 38)	FO1	2 mm	0.01 mm	0-50-0	2,480
		FO2	2 mm	0.01 mm	0-100	2,480
		F51	0.1"	0.001"	0-50-0	2,780
		F52	0.1"	0.001"	0-100	2,780
	UNIVERSAL TEST SET	UI01	2 mm	0.01 mm	0-50-0	4,070
		UI02	2 mm	0.01 mm	0-100	4,070
		UI51	0.1"	0.001"	0-50-0	4,480
		UI52	0.1"	0.001"	0-100	4,480
	TYRE TREAD DEPTH GAUGE	TTG01	8 mm	0.1 mm	-	2,055
		TTG02	0.32"	0.004"	-	2,260
	CRANK SHAFT GAUGE	CS1	60-600 mm	0.01 mm	0-50	7,490
		CS2	2.4"-23.6"	0.0005"	0-20	8,230
	DIAL DEPTH GAUGE	K158/0	0-200 mm	0.1 mm	10-0	3,010
		K158/3	0-200 mm	0.01 mm	100-0	3,410
		K158/1	0-8"	0.001"	100-0	3,750
	DIGITAL DIAL DEPTH GAUGE	K158/DP	0-200 mm/0.8"	0.001 mm/0.00005"	-	13,580
	VERNIER HEIGHT GAUGE	VH300	0-300 mm/0-12"	0.02 mm/0.001"	-	14,940
		VH600	0-600 mm/0-24"	0.02 mm/0.001"	-	25,360
	DIGITAL HEIGHT GAUGE	DH300	0-300 mm/0-12"	0.01 mm/0.0005"	-	23,420
		DH600	0-600 mm/24"	0.01 mm/0.0005"	-	44,240
		DH1000	0-1000 mm/0-40"	0.01 mm/0.0005"	-	74,690
	DOUBLE COLUMN DIGITAL HEIGHT GAUGE	DCDH300	0-300 mm/0-12"	0.010 mm/0.0005"	-	35,620
		DCDH600	0-600 mm/0-24"	0.010 mm/0.0005"	-	53,430
	UNIVERSAL BEVEL PROTRACTOR		0-360°	-	5'	5,990
	PRECISION SPIRIT LEVEL	BSL 150	150 x 44 x 46 mm	0.02 mm/m	-	8,990
		BSL 200	200 x 48 x 46 mm	0.02 mm/m	-	9,400
		BSL 300	300 x 48 x 46 mm	0.02 mm/m	-	11,700